

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
23 June 2005 (23.06.2005)

PCT

(10) International Publication Number
WO 2005/057777 A1

(51) International Patent Classification⁷: **H03B 5/20**

LEWIN, Thomas [SE/SE]; Landstormsvägen 40, S-439
94 Onsala (SE).

(21) International Application Number:

PCT/SE2003/001917

(74) Agent: **ALBIHNS GÖTEBORG AB**; Box 142, S-401 22
Göteborg (SE).

(22) International Filing Date:

10 December 2003 (10.12.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(71) Applicant (for all designated States except US): **TELEFONAKTIEBOLAGET LM ERICSSON** (publ)
[SE/SE]; S-164 83 Stockholm (SE).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(72) Inventors; and

(75) Inventors/Applicants (for US only): **GEVORGIAN, Spartak** [AM/SE]; Adler Salvius gata 15, S-411 11 Göteborg (SE). **JACOBSSON, Harald** [SE/SE]; Fullrigaregatan 10A, S-426 74 VÄSTRA FRÖLUNDA (SE).


(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,

[Continued on next page]

(54) Title: AN OSCILLATOR CIRCUIT WITH TUNEABLE SIGNAL DELAY MEANS



(57) Abstract: The invention discloses an oscillator circuit (100, 200, 300, 400), comprising an oscillating element (110, 210, 310, 410) and output means (115, 215, 315, 415) for outputting an oscillation frequency from the oscillating circuit. The circuit further comprises a signal delay means (120, 220, 320, 420) which is arranged in series with the oscillating element and feeds the output signal back to the oscillating element. The delay means is (120, 220, 320, 420) tuneable with respect to the delay it provides. The oscillating element can be an amplifier or a VCO, and the delay means can be a Delay Locked Loop or a tuneable delay line, depending on the embodiment of the invention.



WO 2005/057777 A1



SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.